

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT USE

■ Used according to manufacturer's directions. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

SUPPLIER

Quick Smart Products Pty Ltd
53 Assembly Drive
Tullamarine Vic 3043 Australia
Telephone: +61 3 9338 6655
Fax: +61 3 9335 2598
Poisons Information Centre 131126

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

POISONS SCHEDULE S5

RISK

- Highly flammable.
- Irritating to eyes and respiratory system.
- HARMFUL - May cause lung damage if swallowed.
- Repeated exposure may cause skin dryness and cracking.
- Vapours may cause drowsiness and dizziness.
- Inhalation, skin contact and/or ingestion may produce health damage*.
- Cumulative effects may result following exposure*.
- May produce skin discomfort*.

* (limited evidence).

SAFETY

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/ fumes/ vapour/ spray.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- Do not empty into drains.
- To clean the floor and all objects contaminated by this material, use water and detergent.
- Keep container tightly closed.
- Keep away from food, drink and animal feeding stuffs.
- In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
- If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).
- This material and its container must be disposed of as hazardous waste.

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	GUN WASH	53 ASSEMBLY DRIVE
Manufacturers Code:	GW5, GW25	TULLAMARINE VIC 3043
Date:	August 2011	ABN: 40 959 725 049
		(03) 9338 6655 (BH)
		(03) 9336 7945 (AH)

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methyl ethyl ketone	78-93-3	>60

Section 4 - FIRST AID MEASURES

SWALLOWED

■ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

■ If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

■ If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

■ Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Do not use a water jet to fight fire.
 - Alcohol stable foam.
 - Dry chemical powder.
 - BCF (where regulations permit).
 - Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.
Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

HAZCHEM

•3YE

Personal Protective Equipment:

Breathing apparatus.

Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapours
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

- Avoid strong bases.
- Ketones in this group:
 - are reactive with many acids and bases liberating heat and flammable gases (e.g., H₂).
 - react with reducing agents such as hydrides, alkali metals, and nitrides to produce flammable gas (H₂) and heat.
 - are incompatible with isocyanates, aldehydes, cyanides, peroxides, and anhydrides.
 - react violently with aldehydes, HNO₃ (nitric acid), HNO₃ + H₂O₂ (mixture of nitric acid and hydrogen peroxide), and HClO₄ (perchloric acid).
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	methyl ethyl ketone (MEK)	150	445	300	890

ENGINEERING CONTROLS

■ For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling	0.5- 1 m/s (100-200 f/min.)

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	GUN WASH	53 ASSEMBLY DRIVE
Manufacturers Code:	GW5, GW25	TULLAMARINE VIC 3043
Date:	August 2011	ABN: 40 959 725 049
		(03) 9338 6655 (BH)
		(03) 9336 7945 (AH)

(released at low velocity into zone of active generation)	
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200-500 f/min.)

PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

GLOVE SELECTION

- Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1 – Occupational Protective Gloves – Selection, Use and Maintenance.

RESPIRATOR

- If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	GUN WASH	53 ASSEMBLY DRIVE
Manufacturers Code:	GW5, GW25	TULLAMARINE VIC 3043
Date:	August 2011	ABN: 40 959 725 049
		(03) 9338 6655 (BH)
		(03) 9336 7945 (AH)

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear colourless highly flammable liquid with a sharp odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

State:	Liquid	Molecular Weight:	Not Applicable
Melting Range (°C):	Not Available	Viscosity:	Not Available
Boiling Range (°C):	Not Available	Solubility in water (g/L):	Immiscible
Flash Point (°C):	-5	pH (1% solution);	Not Applicable
Decomposition Temp (°C);	Not Available	pH (as supplied);	Not Applicable
Autoignition Temp (°C);	Not Available	Vapour Pressure (kPa);	10.133
Upper Explosive Limit (%);	9.5	Specific Gravity (water=1);	0.8
Lower Explosive Limit (%);	1.8	Relative Vapour Density (air=1);	> 1
Volatile Component (%vol);	100	Evaporation Rate;	Not Available

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be damaging to the health of the individual.

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result.

EYE

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	GUN WASH	53 ASSEMBLY DRIVE
Manufacturers Code:	GW5, GW25	TULLAMARINE VIC 3043
Date:	August 2011	ABN: 40 959 725 049
		(03) 9338 6655 (BH)
		(03) 9336 7945 (AH)

- This material can cause eye irritation and damage in some persons.

The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area.

SKIN

- Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

INHALED

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Ketone vapours irritate the nose, throat and mucous membrane. High concentrations depress the central nervous system, causing headache, vertigo, poor concentration, sleep and failure of the heart and breathing. Some ketones can cause multiple nerve disorders, inducing "pins and needles" and weakness in the limbs.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

CHRONIC HEALTH EFFECTS

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

TOXICITY AND IRRITATION

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

- Not available. Refer to individual constituents.

METHYL ETHYL KETONE:

- Unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Oral (rat) LD50: 2737 mg/kg	Eye (human): 350 ppm -Irritant
Inhalation (human) TCLo: 100 ppm/5 m	Eye (rabbit): 80 mg - Irritant
Inhalation (rat) LD50: 23500 mg/m ³ /8 hr	Skin (rabbit): 402 mg/24 hr - Mild
Dermal (rabbit) LD50: 6480 mg/kg	Skin (rabbit):13.78mg/24 hr Open
Inhalation (man) TCLo: 10 mg/m ³ /6 hr - Mild	
Inhalation (rat) LC50: 50100 mg/m ³ /8 hr	
Dermal (rabbit) LD50: 20000 mg/kg	

REPROTOXIN

methyl ethyl ketone	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
---------------------	---	--------------------------------

Section 12 - ECOLOGICAL INFORMATION

- DO NOT discharge into sewer or waterways.
- This material and its container must be disposed of as hazardous waste.

ECOTOXICITY

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
methyl ethyl ketone	LOW	HIGH	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
- Dispose of waste according to Federal, EPA, State and Local Regulations. Assure conformity with all applicable regulations.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID
 HAZCHEM: ●3YE (ADG7)

ADG7:

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043 ABN: 40 959 725 049 (03) 9338 6655 (BH) (03) 9336 7945 (AH)
Product Name:	GUN WASH	
Manufacturers Code:	GW5, GW25	
Date:	August 2011	

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	II
Special provisions:	163	Packing Instructions:	None
Limited quantities:	5 L	Portable tanks and bulk containers - Instructions:	T4
Portable tanks and bulk containers - Special provisions:	TP1; TP8; TP28	Packagings and IBCs - Packing instruction:	P001; IBC02
Packagings and IBCs - Special packing provisions:	PP1		

Name and description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Land Transport UNDG:

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	II

Shipping Name: PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Air Transport IATA:

UN/ID Number:	1263	Packing Group:	II
Special provisions:	A3		

Shipping name: PAINT RELATED MATERIAL

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	II
EMS Number:	F-E, S-E	Special provisions:	163
Limited Quantities:	5 L		

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

Section 16 - OTHER INFORMATION

CONTACT PERSON/POINT

- Technical Information: (03) 9338 6655
- Date of Preparation or Last Revision of MSD: 25 August 2011

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors

GUN WASH

MATERIAL SAFETY DATA SHEET

MSDS No:			QUICK SMART PRODUCTS
Product Name:	GUN WASH		53 ASSEMBLY DRIVE
Manufacturers Code:	GW5, GW25		TULLAMARINE VIC 3043
Date:	August 2011		ABN: 40 959 725 049
			(03) 9338 6655 (BH)
			(03) 9336 7945 (AH)

determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user must review this MSDS in the context of how the product will be handled in the workplace and in conjunction with other materials. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

END OF MSDS