

STAMPING OIL MC

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	STAMPING OIL MC	53 ASSEMBLY DRIVE
Manufacturers Code:	SOMC5, SOMC20, SOMC205	TULLAMARINE VIC 3043
Date:	22 MAY 2006	(03) 9338 6655 (BH) (03) 9336 7945 (AH)

STATEMENT OF HAZARDOUS NATURE: *HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA*

IDENTIFICATION

U/N No	1993	Dangerous Goods Class	3
Hazchem Code	3Y	Poisons Schedule	S5

PHYSICAL DESCRIPTION / PROPERTIES

Appearance:	Colourless to pale yellow	Odour:	Solvent Odour
Autoignition Temperature:	N/A	Flash Point(°C):	35°C (Closed Cup)
Boiling Point (°C):	N/A	Flammability Limits(%):	N/A
Vapour Pressure:	N/A	Solubility in Water:	Insoluble
Specific Gravity (20°C):	APPROX 0.8	Vapour Density:	N/A
Evaporation Rate:	N/A	Percent Volatiles:	N/A
Viscosity	0.8-1.5Cst @ 40°C		

INGREDIENTS:

Contains aliphatic and aromatic hydrocarbons as well as additives.

Chemical Entity	W%W	CAS No:	PROPORTION
NAPHTHA, PETROLEUM, HYDRODESULFURIZED HEAVY		64742-82-1	60-100%
OTHER INGREDIENTS DETERMINED NOT TO BE HAZARDOUS		N/R	BALANCE

SAFE HANDLING INFORMATION

Handling:	Open containers cautiously as contents may be under pressure. Use only in a well ventilated area. Do NOT store or use in confined spaces. Prevent concentration in hollows and sumps. Do not enter these areas until atmosphere has been checked. Do not use near welding or other ignition sources. Build up of mists or vapours in the atmosphere must be prevented. Do not inhale vapours. When dealing with large quantities, repeated or prolonged exposure without protection should be prevented in order to lessen the possibility of disorders. It is essential that all who come into contact with this material, maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or going to the toilet. Keep tank covered and containers sealed when not in use. Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurise or expose to open flame or heat. Keep container closed and bung in place.
Storage:	The product should be stored in a cool, dry, well ventilated area, away from sources of ignition and oxidising agents. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom reference should be made to Australian Standard AS1940 – the storage and handling of flammable and combustible liquids. Reference should also be made to all Local, State and Federal regulations.

STAMPING OIL MC

MATERIAL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	STAMPING OIL MC	53 ASSEMBLY DRIVE
Manufacturers Code:	SOMC5, SOMC20, SOMC205	TULLAMARINE VIC 3043
Date:	22 MAY 2006	(03) 9338 6655 (BH) (03) 9336 7945 (AH)

HEALTH HAZARD INFORMATION

EFFECTS

Swallowed:	Harmful – may cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema. Ingestion may also result in nausea, vomiting, abdominal pain, headache, lethargy, muscular weakness and central nervous system effects, including dizziness, confusion, loss of consciousness that can ultimately proceed to coma and possibly death.
Eye:	Eye contact and high concentrations of vapour may cause eye irritation, including redness, lachrymation and stinging.
Skin:	Extensive and or prolonged skin contact may cause irritation including, itching, redness and a degreasing action on the skin leading to dermatitis.
Inhaled:	Inhalation of vapour can result in similar harmful effects to those of ingestion. ie headaches, dizziness, intoxication, nausea and other central nervous system effects. High concentrations with prolonged use may also lead to unconsciousness and possible death.

TREATMENT

Swallowed:	DO NOT induce vomiting. Immediately wash out mouth with water. SEEK immediate medical attention.
Eye:	If contact with the eye(s) occurs, wash with copious amounts of water for approximately 15 minutes holding eyelids open. Take care not to rinse contaminated water into the non-affected eye. If irritation develops and persists, seek immediate medical attention.
Skin:	Remove all contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. Ensure contaminated clothing is washed before re-use or discard. If irritation develops, seek medical attention.
Inhaled:	Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a facemask if breathing is difficult. If irritation develops and persists, seek IMMEDIATE medical attention.

PRECAUTIONS FOR USE:

Exposure Standards:	No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC). However, as with all chemicals, exposure should be kept to the least possible levels.
Ventilation:	Where vapours or mists are generated and exposure standards are exceeded, the use of respiratory protection, or a flame proof exhaust ventilation system is recommended.
Personal Protection:	Safety glasses or face shield as appropriate. Impervious gloves recommended. Anti static footwear where appropriate. Impervious protective clothing where it is likely to be contaminated.
Flammability:	Flammable. Extinguishing Media. Dry chemical or foam to extinguish fire. Cool fire exposed containers with water/fog spray.

CONTACT POINT

Contact:	Wally Day
-----------------	-----------