

# TYRE GLOSS

## MATERIAL SAFETY DATA SHEET

MSDS No:		<b>QUICK SMART PRODUCTS</b>
Product Name:	Tyre Gloss	<b>53 ASSEMBLY DRIVE</b>
Manufacturers Code:	TG1, TG5, TG25	<b>TULLAMARINE VIC 3043</b>
Page number:	Page 1	<b>(03) 9338 6655 (BH)</b>
Total Pages:	2	<b>(03) 9336 7945 (AH)</b>
Date:	1 May 2007	

**STATEMENT OF HAZARDOUS NATURE:**      *HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA*

### IDENTIFICATION

<b>UN NO:</b>	1300	<b>DANGEROUS GOODS CLASS</b>	3
<b>Hazchem Code:</b>	3ME	<b>POISONS SCHEDULE</b>	5

### PHYSICAL DESCRIPTION / PROPERTIES

<b>Appearance:</b>	Clear liquid	<b>Odour:</b>	Petroleum
<b>Autoignition Temperature:</b>		<b>Flash Point(°C):</b>	31°C
<b>Boiling Point (°C):</b>	190 °C	<b>Flammability Limits(%):</b>	LEL: 1.0% UEL 7.5%
<b>Vapour Pressure:</b>	260mm Hg	<b>Solubility in Water:</b>	Immiscible
<b>Specific Gravity (20°C):</b>	0.78	<b>Vapour Density:</b>	
<b>Solubility – Other:</b>		<b>Percent Volatiles:</b>	>75
<b>Evaporation Rate:</b>		<b>PH @ 20°C:</b>	

### INGREDIENTS:

Chemical Entity	W%W	CAS No:	UN No:
Light Aliphatic Solvent	>60%	8042 47 5	1300
Toluene	<5%	108 88 3	1294

### SAFE HANDLING INFORMATION

<b>Storage &amp; Transport:</b>	This is a flammable product. Store in a cool, dry, well ventilated place. Store away from sources of heat, ignition, sparks and strong oxidising agents. Take precautions against static electricity discharges. Keep away from foodstuffs and food containers. Keep container closed when not in use.
<b>Spills &amp; Leaks:</b>	Shut off all sources of ignition. Clear area of all unprotected personnel. Contain spill with inert absorbent. If possible allow the material to evaporate. Place residue in drums or other suitable containers for disposal.
<b>Waste Disposal:</b>	Dispose of material by conforming with any legislative requirements.
<b>Special Precautions:</b>	Use in well ventilated area. DO NOT use in confined spaces.
<b>Fire &amp; Explosion Data:</b>	Flammable liquid. Burning liquids can emit carbon dioxide and carbon monoxide. Fire fighters should wear self-contained breathing apparatus if there is a risk of exposure to vapour or products of combustion. Fight fires with foam, carbon dioxide or dry chemical powder.
<b>Reactivity:</b>	
<b>Incompatibilities:</b>	

## HEALTH HAZARD INFORMATION

### HEALTH EFFECTS

<b>Swallowed:</b>	Ingestion can lead to nausea, vomiting, irritation to the gastrointestinal tract.
<b>Eye:</b>	A moderate eye irritant. Vapours and mists can irritate the eyes.
<b>Skin:</b>	Contact with the skin may cause irritation and will have a degreasing action on the skin. Repeated or prolonged skin contact with the skin may lead to irritant contact dermatitis.
<b>Inhaled:</b>	Inhalation of vapour or spray mist may cause irritation to mucous membranes and respiratory tract. Inhalation of the product at high concentrations can produce central nervous system depression, loss of co-ordination, impaired judgement even unconsciousness.

### TREATMENT

<b>Swallowed:</b>	If swallowed, immediately rinse mouth with water. Give a glass of water to drink. <b>DO NOT</b> induce vomiting. Seek medical assistance immediately.
<b>Eye:</b>	Immediately flush with large amounts of water for fifteen (15) minutes. Seek medical assistance.
<b>Skin:</b>	Remove contaminated clothing. Immediately wash skin with lots of water. Launder contaminated clothing before re-use. Seek medical assistance if necessary.
<b>Inhaled:</b>	Remove to fresh air. Seek medical assistance. Place patient on their side. Maintain a clear airway. Allow patient to rest and keep warm until recovered. If breathing stops apply artificial respiration immediately.

## PRECAUTIONS FOR USE:

<b>Exposure Standards:</b>	No exposure standard has been assigned for this product. Until one is established, then a suggested Exposure Level is 200ppm. However, all possible consideration should be given to achieving atmospheric concentrations at a level as low as possible.
<b>Ventilation:</b>	Use in well ventilated area. <b>DO NOT</b> use in confined spaces.
<b>Personal Protection:</b>	If ventilation controls do not allow for maintaining atmospheric concentrations below the suggested exposure level, then personal protective equipment must be used. If inhalation risks exist, then the use of an organic vapour respirator, meeting the requirements of AS 1715 and AS 1716 is necessary. Overalls, goggles and gloves should be worn when product is not used in accordance with label instructions.
<b>Flammability:</b>	Flammable liquid. Do not use near naked flame.

## CONTACT POINT

WALTER DAY  
Phone: 9338-6655